

MEGA TILE PASTE

High Quality Tile Adhesive Paste

DESCRIPTION

MEGA TILE PASTE is a ready mixed paste for direct application based on Co-polymer synthetic resin .

ADVANTAGES

- * Ready to use , easy to apply .
- * Can be used on the top of fairface concrete , plaster , gypsum boards , wooden boards , old ceramic tile and old paintings

METHOD OF APPLICATION

- Stir **MEGA TILE PASTE** in the container before use
- Using one side notched trowel , apply a layer to the required thickness .
- Be sure that the tile weight suits the thickness of the adhesive .
- Press , twist the tile on the adhesive layer till you got complete adhesion .
- Do not apply **MEGA TILE PASTE** on a layer area which you can not fix up tiles before 20 minutes
- Do not leave **MEGA TILE PASTE** uncovered in the container or on wall for a long time to prevent the formation of skin layer .
- Close container tightly after application .
- Clean tools after application using water .
- Use a wet sponge for cleaning the tiles.
- Grouting for tiles is recommended (**MEGA TILE GROUT**) .

SURFACE PREPARATION

- Clean surface , remove all loose particles and foreign materials .
- Insure that the surface is leveled .
- Damp the surface before application .

STRENGTH in Construction

TECHNICAL INFORMATION

Density at 25° c	1.55 kg /l .	Consistency	White Paste
Viscosity at 25° c	260 pois	Anti fungus	Fungicide
Dilution	With water if necessary	Binder	Co-polymer synthetic resin

SEFETY REGULATIONS

- * While mixing , protect lungs wearing suitable mask .
- * Protect hands and eyes with gloves and goggles .
- * In case of eye contact wash thoroughly and immediately .

CONSUMPTION

1 –2 kg / m² depends on tile base shape and roughness of substrate .

PACKAGES

5 , 20 kg .

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.