

# MEGA CRACK FLOOR

Two Parts Product For Grouting Cracks

## DESCRIPTION

\* **MEGA CRACK FLOOR** is a two component product, Component A is a special cement base grout in powder form containing selected aggregates, Component B is a liquid containing a synthetic resins and special additives to improve workability and adhesion.

## ADVANTAGES

- \* **MEGA CRACK FLOOR** is recommended for hair cracks in concrete floors and offer a high degree for wear resistance , flexibility and impermeability .
- \* **MEGA CRACK FLOOR** has an excellent adhesion to wide range of all substrate .
- \* **MEGA CRACK FLOOR** has a controlled shrinkage to prevent the formation of cracks

## METHODS OF APPLICATION

- The Cracks should be slightly dampened before application , care must be taken not to create pockets of water.
- Empty the contents of the sack together with the liquid into a container and mix thoroughly and homogeneously.
- Use putty spatula for filling cracks making sure not to create air bubbles.
- Take care not to start cleaning off excess grout either too early , before it has started to set or too late , when it has hardened.

## TECHNICAL INFORMATION

<b>Density at 25° C</b>	1.90 kg/l	<b>Foot traffic</b>	2 hour
<b>Mixture life</b>	Approx. 1 hour	<b>Color</b>	White , colored

### STRENGTH in Construction

**PACKAGES**

Powder 5 kg sacks  
Liquid 1 kg container

**STORAGE**

6 months in sealed packs, under suitable storage conditions.

**TECHNICAL SERVICES**

For further information, on-site assistance and trails, Please contact our technical advisory services.