

MEGA POX ALUMINIUM

Two Component Modified Aluminum Epoxy Paint

DESCRIPTION

* **MEGA POX ALUMINIUM** is a good adhesion, high build, self-priming, modified aluminum epoxy coating for rusted steal surfaces and over most types of coatings and rich primers

ADVANTAGES

- Excellent adhesion to rusted steel and most aged paints
- Provides a reflective and anti-solar film, which reduces heat absorption, ultraviolet rays and weathering attack
- Provides silver decorative, protective coating for steel, rusted steel and old painted surfaces

FIELDS OF APPLICATIONS

- It is used for hand cleaned steel which is being coated for the first time
- Is particularly recommended for repairing rusty steel and for upgrading old deteriorated coating
- Ideal for metal buildings, fences, piping, steel bridges, steel tanks, steel equipment's, steel machinery and trucks
- Can be used as primer and as a final coat

SURFACE PREPARATION AND APPLICATION

- Steel surfaces should be clean and free from oil and grease
- For heavily rusted surfaces, sand blasting is recommended
- Mix the two components of **MEGA POX ALUMINIUM** thoroughly until a fully homogenous mixture is obtained
- For normal protection works, one coat is usually enough, but when surfaces are subjected to high attack and temperature changes, another coat is required
- Sufficient ventilations is recommended in closed rooms
- Apply MEGA POX ALUMINUM using brush, roller or sprayer

STRENGTH in Construction

المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٢٦٩٠٧١٠٧ (٢٠٢) فاكس: ٢٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور ،المنطقة الصناعية الأولى ،مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢) المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢) فاكس: ٢٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور ،المنطقة الصناعية الأولى ،مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢) المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٢٩٩٠٥٢٢ (٢٠٢) فاكس: ٢٦٩٠٧١٠٨ (٢٠٢) مصنع: مدينة العبور ،المنطقة الصناعية الأولى ،مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢) المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٢٩٩٠٥٢٢ (٢٠٢) مصنع: مدينة العبور ،المنطقة الصناعية الأولى ،مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢) مصنع: مدينة العبور ،المنطقة الصناعية الأولى ،مصر - هاتف: ٤٤



TECHNICAL INFORMATION

Density at 25° C	1.19 ± 0.02 kg/L	Color	Silver
Rate of consumption	200-250 gm/m2/coat	Initial setting time at 25° C	6-8 hours
Pot life at 25° C	2.5-3 hours	Final setting time at 25° C	24 hours
Solid content	86 %	Full hardness at 25° C	7 days
Temperature resistance	140 ° C	Application of second coat	24 hours

PACKAGES

1 kg, 4 kg (two components)

STORAGE

6months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.

STRENGTH in Construction