

MEGA TILE POX

Non Shrink Epoxy Adhesive Mortar For Ceramic Tiles

DESCRIPTION

- * **MEGA TILE POX** is a three components solvent free epoxy mortar, two components in a liquid form and one dry component
- * High resistant for chemicals

FIELDS OF APPLICATIONS

- Chemical resistance adhesive mortar for fixing anti acid tiles
- Adhesive for steel to concrete and concrete to concrete
- For fixing the anchorage of bolts, grouting under machine plates and steel structures
- Fixing traffic eye cat
- Repair of concrete structures subjected to high static and dynamic loads

SURFACE PREPARATION

- Substrate must be sound, dry and free from oil or grease
- All loose materials and laitance should be removed
- Pour component (B) completely into component (A) and mixing both thoroughly until a fully homogeneous mixture is obtained.
- Add component (C) to epoxy mixture, then mix thoroughly using suitable mixer for at least 3 minutes prior to application

TECHNICAL INFORMATION

Density at 25° C	2.00 ± 0.1 kg/L	Compressive Strength	400-600 kg/cm2
Color	Grey	Flexural Strength	350 kg/cm2
Solid Content	100 %	Mixing Ratio	1:2:10 (A:B:C)
Initial Setting Time	24 hours	Processing Time	45 minutes
Final Setting Time	7 days		

STRENGTH in Construction

المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٣٦٩٠٧١٠٧ (٢٠٢) فاكس: ٣٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور، المنطقة الصناعية الأولى، مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢)
Head Office: 85 El Merghany St., Heliopolis, Cairo Tel: (202) 26907107 Fax: (202) 26907108 - Factory: El Obour City, Industrial Zone I, Egypt Tel: (202) 44891522

PACKAGES

26 kg (three components)

STORAGE

6months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.