

MEGA BACKING ROD

Neoprene Joint Sealant Backing Rods

DESCRIPTION

MEGA BACKING ROD is an elastic neoprene backing rods. It's produced in various dimensions and cross sections to suit all joints. It is used as a backer to support cold applied joint sealants, used within - 40° C to + 70° C

FIELD OF APPLICATIONS

According to specific dimensions of the joints, joint sealant materials must be laid in the joints, and in order to fulfill their functional requirements, **MEGA BACKING ROD** is used as a base to control the required depth of the sealant materials

ADVANTAGES

- High elasticity to insure sufficient fixing to the sides of the joint and prevent seepage of the sealant through the joint
- Controls the depth of the joint, thus saving the quantity of the joint sealant material used
- Does not absorb water or affected by weathering conditions
- Does not stick to sealant
- Easy to cut and fix inside the joint
- Produced in several dimensions and cross sections

DIRECTION OF USE

- Clean the sides of the joint before fixing **MEGA BACKING ROD**
- Fix the depth of the sealant material
- The diameter or the width of **MEGA BACKING ROD** must be greater than the width of the joints by about 25 %
- Push the **MEGA BACKING ROD** by a piece of wood

STRENGTH in Construction

DIMENSIONS

10,15,20,30,50 mm circular rods

PACKAGES

Roll 100 L.M

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.