

MEGA LUX ACRYLIC

High Quality Plastic Emulsion Paint For Interior

DESCRIPTION

* **MEGA LUX ACRYLIC** is a matt Polyvinyl Acrylic base emulsion paint for interior use

ADVANTAGES

- * Very high hiding power due to high percentage of very good quality titanium dioxide
- * Good abrasion resistant .high washability.
- * Good adhesion to all kind of substrate such as plaster ,concrete , wood , gypsum board ,old plastic, alyked paint etc.
- * Resists the effect of U.V. rays , atmospheric condition .
- * **MEGA LUX ACRYLIC** is durable , flexible for all kind of surfaces.
- * Very high hiding power with low consumption rate .
- * Fast drying ,flat ,white color resists yellowing .

METHOD OF APPLICATION

- * Substrate should be clean , free of dust , oils , etc..
- * To be mixed thoroughly before use
- * Under coats to be diluted 10 % - 15 % with water .
- * For best results apply 2 coats of **MEGA LUX ACRYLIC** .
- * Apply necessary putty **MEGA PASTE** for leveling and smoothing between coats .
- * Can be applied by brush roller or sprayer .
- * Drying time for re-coating 2 - 4 hours .

STRENGTH in Construction

TECHNICAL INFORMATION

| | | | |
|---------------------------|--------------------|----------------------------|-------------------------------|
| Density at 25 °C | 1.51 ± 0.03 kg / l | Appearance | White and colored |
| Touch dry at 25 °C | 2 – 4 hours | pH | 8 – 8.5 |
| Final dry at 25 °C | 18 - 24 | Solid content | 66% ± 1% |
| Dry film Thickness | 100 : 125 micron | Rate of consumption | 6-8m ² / kg / coat |

CONSUMPTION

1 kg covers 6 – 8 sq.m per coat

PACKAGES

5, 15 , 20 kg packs

STORAGE

12 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.