

MEGA PASTE

Ready To Use Interior And Exterior Putty

DESCRIPTION

- **MEGA PASTE** specially formulated putty based on vinyl acrylic emulsion
- For smoothing cement base surfaces (plasters , concrete , etc..) Prior to painting procedure.
- For treating surface imperfections between painting coats.

ADVANTAGES

- * Compatible with all under and finish coating paints.
- * Perfect bond strength to all substrates.
- * Ready to use, easy to apply and easy to sand
- * For perfect smooth finish, free of holes, cracks and irregularities with minimum thickness putty According to surface roughness.

METHOD OF APPLICATION

- * Substrates should be clean, free of dust and oils.
- * Absorbent surfaces to be moistened with water or sealed with **MEGA BOND** solution according to substrate conditions
- * To be applied by hand pressed putty knife or plaster trowel.
- * Each coat to be sanded before applying a further coat.
- * For exterior use, it is preferable to apply finish coats directly after puttying.
- * It is recommended not to leave the paste without coverage for a long period

TECHNICAL INFORMATION

Density at 25° C	1.75 kg \ l	Appearance	white paste
Viscosity at 25° C	120 poise	Composition	vinyl - acrylic resins , selected filler and additives

STRENGTH in Construction

المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٣٦٩٠٧١٠٧ (٢٠٢) فاكس: ٣٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور، المنطقة الصناعية الأولى، مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢)
Head Office: 85 El Merghany St., Heliopolis, Cairo Tel: (202) 26907107 Fax: (202) 26907108 - Factory: El Obour City, Industrial Zone I, Egypt Tel: (202) 44891522

CONSUMPTION

300 - 350 gm / m² / coat depending on the roughness of substrate

PACKAGES

1 kg	plastic can
5 kg	plastic can
20 kg	plastic bag

STORAGE

9 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.