

MEGA PLASTIC SUPER

Plastic Emulsion Paint For Economical Use

DESCRIPTION

• MEGA PLASTIC SUPER is a matt acrylic base, plastic paint

ADVANTAGES

- * Good coverage power with low consumption rate
- * For internal and external use on concrete, plaster, gypsum, masonry, wood etc..
- * Very economical, fast drying and recoat able same day.
- * Stable against U.V. and does not change the color
- * To be used as a sub-base coat for emulsion and enamel paint
- * Can be used as a final coat for interior surfaces for economic use.

DIRECTION FOR USE

- Surface must be clean and free from dust and oil
- MEGA PLASTIC SUPER should be stirred before use
- Smoothing surface with MEGA PUTTY to fill all cavities
- For porous surface apply a primer coat of MEGA PLASTIC SUPER diluted with water in the ratio of 15% 20%
 Apply one or two coats of MEGA PLASTIC SUPER according to the requirement

TECHNICAL INFORMATION

Density at 25° C	1.45 kg/l	Color	White, colored
Touch dry	1 hour	Recoat	2-4 hours

CONSUMPTION

5 - 6 m2/kg/coat

PACKAGES

5 kg, 15 kg, 20 kg



STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.