

MEGA PLASTIC

Plastic Emulsion Paint For Economical Use

DESCRIPTION

- **MEGA PLASTIC** is a matt acrylic base , plastic paint

ADVANTAGE

- * Good coverage power with low consumption rate
- * For internal use on concrete, plaster, gypsum, masonry, wood etc..
- * Very economical, fast drying and recoatable same day.
- * To be used as a sub-base coat for emulsion paint
- * Can be used as a final coat for interior surfaces for economic use

DIRECTION OF USE

- Surface must be clean and free from dust and oil
- **MEGA PLASTIC** should be stirred before use
- Smoothing surface with **MEGA PUTTY** to fill all cavities
- For porous surface apply a primer coat of **MEGA PLASTIC** diluted with water in the ratio of 15% - 20%
- Apply one or two coats of **MEGA PLASTIC** according to the requirement

TECHNICAL INFORMATION

Density at 25° C	1.55±0,02 kg/l	Color	White, colored
Touch dry	1 hour	Recoat	2-4 hours

STRENGTH in Construction

CONSUMPTION

4 - 6 m²/kg/coat

PACKING

5 kg, 15 kg, 25 kg

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.

STRENGTH in Construction

المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٣٦٩٠٧١٠٧ (٢٠٢) فاكس: ٣٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور، المنطقة الصناعية الأولى، مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢)
Head Office: 85 El Merghany St., Heliopolis, Cairo Tel: (202) 26907107 Fax: (202) 26907108 - Factory: El Obour City, Industrial Zone I, Egypt Tel: (202) 44891522

Email: info@intradechemicals.com www.intradechemicals.com