

MEGA STAR S

Semi-Gloss Synthetic Paint

DESCRIPTION

- **MEGA STAR S** is a semi-gloss synthetic enamel, alkyd resin paint
- **MEGA STAR S** is available in very wide range of colors
- High hiding power ,smooth and glossy appearance .
- Produces elastic homogenous film, well adhered to substrate, resistant to abrasion, water and weathering conditions.

FIELDS OF APPLICATIONS

- * Air drying enamel paint for exterior and interior use.
- * Wood and metal doors
- * To apply on all kind of cementations and gypsum surfaces

METHOD OF APPLICATION

* PRECOATED SURFACE

- Stir the product before use
- Surface should be clean, free of dust or dirt's
- Apply one or two coat of **MEGA STAR S**

NEW SURFACE

- Surface may be smoothened by putty (**MEGA PASTE**)
- Apply two coats of **MEGA STAR S**, the second coat to be applied after complete drying of the first coat
- **MEGA STAR S** can be used by brush, roller or sprayer
A well ventilation should be carried out before application

STRENGTH in Construction

TECHNICAL INFORMATION

Density at 25° C	1.20 kg/l	Solid Content	82% ± 1%	Color	White and colored
Surface dry at 25° C	4 hours	Hard dry	24 hours	Viscosity	5 min.
Time of second coat	12 hours	Dry film thickness	Spry 15 micron Roll 150 micron	Rate of consumption	7-9 m ² /kg

CONSUMPTION7-9 m²/kg/coat**PACKAGES**

1 kg, 4 kg, 5 kg

STORAGE

1 year in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.