

MEGA TONE

High Quality Silk Paint

DESCRIPTION

- **MEGA TONE** semi – gloss latex smooth paint based on concrete styrene acrylic and high quality titanium dioxide.

ADVANTAGES

- * Semi gloss with silk appearance for interior and exterior use.
- * Intense white and its color does not change with time.
- * High coverage power with low consumption rate.
- * Extremely washable with high resistance to atmospheric conditions.
- * Fast drying with excellent resistance to cracking and peeling

METHOD OF APPLICATIONS

- Substrate should be clean, free of dust, oils, etc.
- To be mixed thoroughly before use.
- Under coats to be **MEGA TONE** diluted 20 % - 30 % with water or **MEGA PLASTIC SUPER** or **MEGA COAT**.
- Finish coat to be diluted 10% - 15 % with water.
- Apply necessary putty for leveling and smoothing between coats.
- Can be applied by brush roller or sprayer.

TECHNICAL INFORMATION

Density at 25° C	1.25 ±0.02 kg/l	Color	White and colored
pH at 25° C	7.5 – 8.5	Dry Time at 25° C	55 – 60 min

CONSUMPTION

1 kg covers 7 –9 sq.m per coat

STRENGTH in Construction

PACKAGES

- 5, 15, kg packs.

STORAGE

8 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.