

MEGA ZINC PRIMER

High Quality Primer

DESCRIPTION

* **MEGA ZINC PRIMER** is a modified zinc phosphate anticorrosive primer

ADVANTAGES

- * Does not require skilled labour.
- * Ready to use or it can be diluted up to 10 % with **MEGA THIENER no. 7**.

FIELDS OF APPLICATIONS

- * It is ideal for areas where thoroughly preparations can not be undertaken and has excellent adhesion ability on steel and iron surfaces

DIRECTION FOR USE

- * The surfaces must be clean and dry.
- * Remove rust by wire brushing or sand blasting .
- * Apply one coat of primer when other topcoats are to be used.
- * It is recommended to use a second coat of primer when no further topcoats to be applied

TECHNICAL INFORMATION

Density at 25° C	1.28 ± 0.01 kg\l	Color	Grey
Viscosity at 25 °C	80 sec (FC\ 4)	Surface dry	2 hours approx.
Solid content	60 %	Hard dry	24 hours

STRENGTH in Construction

CONSUMPTION

* 8–10 m² / kg

To have wet film thickness 100 microns and dry film thickness 70 microns

PACKAGES

* 1 kg , 5 kg , 20 kg

STORAGE

* 12 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.