

MEGA BITUMEN RUBBER

Bitumen Latex Emulsion

DESCRIPTION

- **MEGA BITUMEN RUBBER** water based , cold applied bitumen emulsion latex complied with Din 18 195 part 2
- Dries to form a rubber elastic membrane for water proofing of roofs , under ground structures , foundations , water tanks ,showers , swimming pools .
- **MEGA BITUMEN RUBBER** has up to 900 % expansion properties (depending on film thickness).
- **MEGA BITUMEN RUBBER** does not develop any gases which can be hazardous to health during application .
- **MEGA BITUMEN RUBBER** is very good adhesive for plastic sheets , styrofoams ,etc. form

ADVANTAGES

- * Cold , clean , and dry application.
- * Economical cost comparing to hot applied bitumen .
- * Can be used on damp surfaces.
- * Protective coating against aggressive salts and chemical in soil and underground water .
- * Good adhering to all surfaces , concrete ,steel ,wood etc..

INSTRUCTIONS OF USES

- Surface should be clean , free of dust and impurity .
- Stir well before use and apply primer coat diluted with water at ratio of 1:2.
- After 3 hours apply subsequent coating (2 or 3 coats) .
- For subsequent coating it may be diluted with 10 –20 % of water .
- Thinning should be only with water.

TECHNICAL INFORMATION

Density at 25° C	1.00 kg/l	Drying time	2 hours
pH	9 – 11	Over coating time	3 hours

STRENGTH in Construction

المكتب الرئيسي: ٨٥ ش الميرغنى، مصر الجديدة، القاهرة - هاتف: ٣٦٩٠٧١٠٧ (٢٠٢) فاكس: ٣٦٩٠٧١٠٨ (٢٠٢) - مصنع: مدينة العبور، المنطقة الصناعية الأولى، مصر - هاتف: ٤٤٨٩١٥٢٢ (٢٠٢)
Head Office: 85 El Merghany St., Heliopolis, Cairo Tel: (202) 26907107 Fax: (202) 26907108 - Factory: El Obour City, Industrial Zone I, Egypt Tel: (202) 44891522

CONSUMPTION

* For waterproofing coating 1- 2 kg / m²

PACKAGES

* 4 kg , 15 kg , 200 kg

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.